



Measuring for Custom Suits

If you are visiting a tailor to obtain these measurements, take careful note of the pants instructions as they differ from the way many tailors measure. Follow the directions below and write the measurement's safe keeping.

*Instructions with detailed photos can be found at:
<http://www.weddingtropics.com/help/suit.html>*

COAT LENGTH

Standing upright measure from the upper end of the shoulder where it joins the neck to the length desired. Alternately, you can also double-check this measurement on one of your own jackets. Take measurement from the collar to the bottom of your jacket as pictured. The two measurements should be the same.

Coat Length measurement (in inches) _____

SHOULDER

From the back and standing up straight, measure from shoulder seam to shoulder seam.

Shoulder measurement (in inches) _____

SLEEVE

Measure from shoulder seam to the bottom of the sleeve cuff.

Sleeve Measurement (in inches) _____

CHEST

Measure all the way around the chest, directly under the armpits with arms relaxed.

Chest Measurement (in inches) _____

BELLY

Measure around the widest part of the stomach.

Belly Measurement (in inches) _____

WAIST

Measure around the waist where your pants normally sit.

Please note this measurement will be larger than the label size that you usually buy.

Waist Measurement (in inches) _____

OUTSEAM

Measure from the very top of the waistband to the very bottom of the pants leg.

Type the word FIX after this measurement.

Outseam Measurement (in inches) _____

FRONT RISE

Measure from the very top of the waistband to where all the seams meet at the crotch.

Type the word FIX after this measurement.

Front rise Measurement (in inches) _____

HIP/SEAT

Lay pants flat with front side up eliminating any slack. Measure the distance across the widest point between top of waist and crotch seam. (Approximately 9" down from top of waist or just below the zipper line)

Multiply this number by 2.

Type the word FIX after this measurement.

Hip seat Measurement (in inches) _____

THIGH

Lay your pants completely flat. Measure the widest part of the thigh. **Multiply this number by 2.**

Type the word FIX after this measurement.

Thigh Measurement (in inches) _____

LEG CUFF OPENING

Lay your pants completely flat with front side up. Measure the distance across finished opening at bottom of pants legs. **Multiply this number by 2.**

Type the word FIX after this measurement.

Leg Cuff Measurement (in inches) _____